



WB10

- ✓ MTP WB10 is designed for wheel loaders
- ✓ Non-directional pattern provides excellent grip and traction on rocky surfaces
- ✓ The rock flush pattern and shoulder protector provides excellent cut resistance



- Special Tread Compound
- Reinforced Inner Liner
- Higher Turn Up Construction
- Flat Base Bead Construction



Size	TRA Code	Load Symbol	Max. Speed (km/h)	Load Index	Standard Rim	Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity (kg)	Cold Inf. Pressure (kPa)	Weight (kg)
20.5R25	L5	**	10	193A2	17.00/2.0	70	1550	520	11500	650	638
23.5R25	L5	**	10	201A2	19.50/2.5	78	1675	595	14500	650	460
26.5R25	L5	**	10	209A2	22.00/3.0	88	1800	675	18500	650	616
29.5R25	L5	**	10	216A2	25.00/3.5	96	1920	750	22400	650	778

MTP Tyres

P.O. Box 436
5140 AK Waalwijk
The Netherlands

Elzenweg 7
5144 MB Waalwijk
The Netherlands

Phone: +31 416 82 00 32
Fax: +31 416 82 00 33
info@universaltyretrading.com

WWW.MTPTYRES.COM